



DW-970A

Product Description

- Single-Coated Conductive Adhesive Tape.
- Material Is AL-Foil.
- Excellent Electrical Resistance And For Bonding Display Modules Of LCD Part.

Product Structure

	AL-Foil (50 μ m)
	Conductive Acrylic Adhesive
	Release Liner

Technical Data

Classification		Unit	Value	Test Method
Thickness	Backing	μ m	50 \pm 2	KS T 1028
	Total		80 \pm 5	
Peel Strength		g/25mm	1200 \pm 100	
Electrical Resistance		Ω	0.1 \downarrow	Hioki 3540 500g Pressure
Holding Power		mm/hr	0.1	SUS 304 1kg
Heat Resistance		$^{\circ}$ C	Good	110 $^{\circ}$ C \times 500g Heating oven

Dimensions

Roll Width (mm)	Roll Length (M)

Shelf Life

Product retains its performance and properties for 12 months from date of manufacture when stored in original cartons at room temperature & 50%RH

Company

436-8 Songma-Ri,
Daegot-Myeon, Gimpo-Si
Kyungki-Do, KOREA
TEL(82)-31-982-1999
FAX(82)-31-982-1145

www.dwc1999.com

The information given and the recommendations made herein are based on our experience and are believed to be accurate. No guarantee as to, or responsibility for, their accuracy can be given or accepted and no statement made herein is to be treated as a representation or warranty. In every case we urge and recommend that purchasers before using any product make their own tests to determine, to their own satisfaction, its suitability for their particular purposes under their own operating conditions. Such as evaluation should be repeated if materials are changed in any way or bought from a different source. No agent or representative of our has any authority to vary, omit or otherwise alter these terms.